



	EL-WIFI	EL-MOTE (new series – SEP 2018)
		
<i>Battery</i>	Rechargeable (8-10 hours by micro USB charger)	AA battery x 4
<i>Battery Life</i>	~ 6 months (for transmission of data every 1 hour)	~ 1 year (for transmission of data every 1 hour)
<i>Onsite Alarm</i>	Flashing alarm symbol on display	LED indicator and sounder (can be disabled)
<i>Onsite spot check</i>	Display	Read by mobile app via NFC (Android only)
<i>Dual Channel option</i>	available but device unit is different from the single channel model	same device unit can be used for both single and dual channel on temperature probe
<i>Setup</i>	EasyLog Cloud: Smartphone App (both Android & iOS) PC software: USB connection to computer	By Smartphone App (both Android & iOS)
<i>Monitor by EasyLog Cloud</i> <i>(for remote monitoring and instant email alert)</i>	✓	✓
<i>Monitor by PC software</i> <i>(for local monitoring only)</i>	✓	✗
<i>Measuring options</i>	<ol style="list-style-type: none"> 1. T+RH (internal) 2. T (internal) 3. Thermistor probe (1M external, 5M & 10M optional extension cable available) 4. Thermocouple probe (1.5M external) 	<ol style="list-style-type: none"> 1. T+RH (2M external probe) 2. T (external) 3. Thermistor probe (3M external probe) ** 2 & 3 are interchangeable 4. Thermocouple probe (1.5M external)